

MSB Pro Server



Modell:	MSB Pro Server FXDBI-2X30-R3
Gehäuse:	Chenbro 19" 3HE Rack RM31408
Mainboard:	Intel Server Mainboard SE7525RP2 Supports up to two Intel® Xeon™ Processors FSB 800 MHz Intel® E7525 Chipset Super I/O Controller National Semiconductor PC87427 Supports up to 8 GB of Registered ECC DDR 400 SDRAM
Steckplätze:	2 x PCI-X 66 Slots 2 x PCI 32-bit/33 MHz Slots 1 x PCI Express x4 Slot 1 x PCI Express x16 Slots
CPU:	Intel® Xeon™ 3,0 GHz FSB 800 MHz 2M
RAM:	2 x 1GB 400MHz DDR ECC Registered
Grafikkarte:	ATI® RAGE™ XL SVGA PCI Graphics Controller 8 MB Frame Buffer of Video Memory
Netzwerkkarte:	1 GbE LAN Controller Intel® PRO/1000 Server Adapter 1 GbE LAN Controller Intel® PRO/1000 GT
Festplatte:	2 x 80 GB Hitachi Deskstar 7K80 S-ATA II 6 x 250 GB Western Digital WD2500JS S-ATA II
Tape:	-
CD/DVD-ROM:	DVD-ROM
Floppy:	ja
Laufwerks-Einschübe:	extern: 2 x 5 1/4" 1 x 3,5" 8 x 3,5" HDD HotSwap
RAID-Adapter:	1 x Dual-Channel S-ATA Controller RAID 0 and 1 1 x 8-Port S-ATA RAID Controller Promise EX8350 3,0 Gb/s per Port, RAID 0, 1, 5, 6, 10, 50, JBOD
Backplane:	2 x 4 Port S-ATA II Chenbro Backplane
Netzteil:	350 W, 2+1 Redundant
Abmessung:	[TxBxH] 660 mm x 422 mm x 132 mm
Betriebssystem:	RedHat EL 4/Cluster
Anwendungen:	OpenExchange, File-Druck-Server, DC

MSB Mikrocomputer Software
HandelsGmbH
Kirchengasse 7
A-1070 Wien

Fon +43-1-526 48 25
Fax +43-1-526 48 25-25

Mail info@msb.co.at
Web www.msb.co.at



Hummingbird Connectivity Business Alliance Partner
Microsoft OEM für System Builder
Red Hat Ready Business Partner
Intel Product Integrator
Kaspersky Certified Partner
SEP Registered Partner